

SAFETY DATA SHEET

1. Identification

Product identifier GRAFOIL® Flexible GTC based

Other means of identification

SDS number 0015

Recommended use Gasket material, automotive, 95% carbon.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier NeoGraf Solutions, LLC

11709 Madison Ave. Lakewood, OH 44107 +1 216-529-3777

Contact person Product Responsibility Manager +1 216-529-3724

E-mail info@neograf.com

Emergency telephone

number

For Chemical Emergency ONLY, call 3E at:

+1-866-519-4752, +1-760-476-3962

Access Code: 333366

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The substance does not meet the criteria for classification.

Precautionary statements

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Graphite		7782-42-5	> 95
Impurity: Crystalline silica (quartz)		14808-60-7	< 0.8

Composition commentsAll concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

GRAFOIL® Flexible GTC based SDS Canada

943641 Version #: 01 Revision date: - Issue date: 25-April-2018

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Most important

symptoms/effects, acute and

delayed

Rinse mouth. Get medical attention if symptoms occur. Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Specific hazards arising from the chemical

Special protective equipment

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters

Fire fighting

Use water spray to cool unopened containers.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste

disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places

where dust is formed. Do not breathe dust. Avoid prolonged exposure.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see section 10 of

the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
Impurity: Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada, Alberta OELs (Occupation	onal Health & Safety Code, Sch	nedule 1. Table 2)	

Canada. Alberta OELs (Occupation Components	Type	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable.
Impurity: Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.

GRAFOIL® Flexible GTC based SDS Canada

943641 Version #: 01 Revision date: -Issue date: 25-April-2018

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable.
Impurity: Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form	
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.	
Impurity: Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
Impurity: Crystalline silica	TWA	0.1 mg/m3	Respirable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Туре	Value	Form	
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable dust.	
Impurity: Crystalline silica	TWA	0.1 mg/m3	Respirable dust.	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protectionUse a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Graphite foil
Physical state Solid.
Form Solid.
Colour Black.

Odour Slight hydrocarbon.

Odour threshold Not available. pH Not applicable.

Melting point/freezing point > 2760 °C (> 5000 °F) / Not applicable.

Initial boiling point and boiling

range

Not applicable.

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) Not available.

GRAFOIL® Flexible GTC based SDS Canada

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not applicable.

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%)

Explosive limit - upper

(%)

Not available. Not available.

Not applicable. Vapour pressure Vapour density Not applicable. Relative density 0.8 - 1.8 (21°C)

Solubility(ies)

< 0.1 % Insoluble Solubility (water) Partition coefficient Not applicable. (n-octanol/water)

Auto-ignition temperature Not applicable. **Decomposition temperature** Not applicable. **Viscosity** Not applicable.

Other information

70 lb/ft3 **Bulk density**

Explosive properties Not explosive. **Oxidising properties** Not oxidising. Percent volatile Not applicable.

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Chlorine. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Test Results Components **Species**

Graphite (CAS 7782-42-5)

Acute

Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

GRAFOIL® Flexible GTC based SDS Canada

943641 Version #: 01 Revision date: -Issue date: 25-April-2018

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with

silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer

risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Risk of cancer cannot be excluded with prolonged

exposure.

ACGIH Carcinogens

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Impurity: Crystalline silica (quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Impurity: Crystalline silica (quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this substance.

Bioaccumulative potential No data available.

Mobility in soil The product is insoluble in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

GRAFOIL® Flexible GTC based SDS Canada

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

country(s).

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

GRAFOIL® Flexible GTC based

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

943641 Version #: 01 Revision date: -Issue date: 25-April-2018 6/7

16. Other information

Issue date 25-April-2018

Revision date - Version No. 01

Disclaimer N

NeoGraf Solutions cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

GRAFOIL® Flexible GTC based SDS Canada