NEOGRAF* SOLUTIONS

SAFETY DATA SHEET

1. Identification

Product identifier GRAFOIL® Flexible GTC based

Other means of identification

SDS number 0015

Recommended use Gasket material, automotive, 95% carbon.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier NeoGraf Solutions, LLC

11709 Madison Ave. Lakewood, OH 44107 +1 216-529-3777

Contact person Product Responsibility Manager +1 216-529-3724

E-mail info@neograf.com

Emergency telephone

number

For Chemical Emergency ONLY, call 3E at:

+1-866-519-4752, +1-760-476-3962

Access Code: 333366

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The substance does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Graphite		7782-42-5	> 95
Impurity: Crystalline silica (quartz)		14808-60-7	< 0.8

Composition commentsAll concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

GRAFOIL® Flexible GTC based SDS US

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Most important

symptoms/effects, acute and

delayed

Rinse mouth. Get medical attention if symptoms occur. Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste

disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places

where dust is formed. Do not breathe dust. Avoid prolonged exposure.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10

of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Туре	Value	
Impurity: Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	Form
Graphite (CAS 7782-42-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910	0.1000)	-	
Components	Туре	Value	Form
Graphite (CAS 7782-42-5)	TWA	15 mppcf	
Impurity: Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

GRAFOIL® Flexible GTC based SDS US

943641 Version #: 01 Revision date: -Issue date: 25-April-2018

US. ACGIH Threshold Limit Values		
Components	Туре	Value

Form Graphite (CAS 7782-42-5) TWA 2 mg/m3 Respirable fraction. Impurity: Crystalline silica **TWA** 0.025 mg/m3 Respirable fraction. (quartz) (CAS 14808-60-7)

US. NIOSH: Pocket Guide to Chemical Hazards

Components Value **Form Type** Graphite (CAS 7782-42-5) **TWA** 2.5 mg/m3 Respirable. Impurity: Crystalline silica **TWA** 0.05 mg/m3 Respirable dust. (quartz) (CAS 14808-60-7)

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

Use a particulate filter respirator for particulate concentrations exceeding the Occupational Respiratory protection

Exposure Limit.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Graphite foil Solid. **Physical state Form** Solid. Color Black.

Odor Slight hydrocarbon.

Odor threshold Not available. pН Not applicable.

Melting point/freezing point > 5000 °F (> 2760 °C) / Not applicable.

Initial boiling point and boiling

range

Not applicable.

Not applicable. Flash point Not applicable. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not applicable.

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Not applicable. Vapor pressure

Vapor density Not applicable. 0.8 - 1.8 (21°C) Relative density

Solubility(ies)

Solubility (water) < 0.1 % Insoluble

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperatureNot applicable.Decomposition temperatureNot applicable.ViscosityNot applicable.

Other information

Bulk density 70 lb/ft³

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Percent volatile Not applicable.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Respiratory sensitization

Acute toxicity

Components Species Test Results

Graphite (CAS 7782-42-5)

Acute Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Skin sensitization This product is not expected to cause skin sensitization.

Not a respiratory sensitizer.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

GRAFOIL® Flexible GTC based SDS US

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Impurity: Crystalline silica (quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Impurity: Crystalline silica (quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) Impurity: Crystalline silica (quartz) (CAS 14808-60-7) Cancer

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects**

No data is available on the degradability of this substance.

12. Ecological information

Ecotoxicity

Mobility in soil

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data available.

Bioaccumulative potential

The product is insoluble in water.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

GRAFOIL® Flexible GTC based 5/7

943641 Version #: 01 Revision date: -Issue date: 25-April-2018 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Graphite (CAS 7782-42-5)

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Graphite (CAS 7782-42-5)

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Graphite (CAS 7782-42-5)

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

US. Rhode Island RTK

Graphite (CAS 7782-42-5)

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

California Proposition 65



WARNING: This product can expose you to Impurity: Crystalline silica (quartz), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Impurity: Crystalline silica (quartz) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Impurity: Crystalline silica (quartz) (CAS 14808-60-7)

GRAFOIL® Flexible GTC based SDS US

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Philippine Inventory of Chemicals and Chemical Substances (PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

Issue date 25-April-2018

Revision date - Version # 01

NFPA ratings

Philippines



Disclaimer

NeoGraf Solutions cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

GRAFOIL® Flexible GTC based SDS US

Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).