NeoGraf SOLUTIONS

SAFETY DATA SHEET

1. Identification

Product identifier GRAFOIL® Injectable Packing Containing Oil

Other means of identification

SDS number 0017

Recommended use Thermal interface.

Workers (and your customers or users in the case of resale) should be informed of the potential **Recommended restrictions**

> presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier NeoGraf Solutions, LLC

> 11709 Madison Ave. Lakewood, OH 44107 +1 216-529-3777

Contact person Product Responsibility Manager +1 216-529-3724

E-mail info@neograf.com

Emergency telephone

number

For Chemical Emergency ONLY, call 3E at:

+1-866-519-4752, +1-760-476-3962

Access Code: 333366

2. Hazard(s) identification

Not classified. **Physical hazards** Not classified. **Health hazards OSHA** defined hazards Not classified.

Label elements

Hazard symbol None. Signal word None.

Hazard statement The substance does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Graphite		7782-42-5	> 80
Synthetic Hydrocarbon Oil		N/A	< 20
Crystalline silica (quartz)		14808-60-7	< 0.8
Triphenyl phosphate		115-86-6	< 0.2

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire. Unsuitable extinguishing media

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places Precautions for safe handling

where dust is formed. Do not breathe dust. Avoid prolonged exposure.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Value

8. Exposure controls/personal protection

Occupational exposure limits

Components

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Type

Components	Type	Value	
Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air	r Contaminants (29 CFR 1910.	1000)	
Components	Type	Value	Form
Graphite (CAS 7782-42-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Triphenyl phosphate (CAS	PEL	3 mg/m3	
115-86-6)			

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Graphite (CAS 7782-42-5)	TWA	15 mppcf	
US. ACGIH Threshold Limit Value	s		
Components	Type	Value	Form
Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
Triphenyl phosphate (CAS 115-86-6)	TWA	3 mg/m3	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Type	Value	Form
Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
Triphenyl phosphate (CAS 115-86-6)	TWA	3 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelinesOccupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

US - California OELs: Skin designation

Triphenyl phosphate (CAS 115-86-6)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

Respiratory protectionUse a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Black paste.

Physical stateSolid.FormPaste.ColorBlack.

Odor Slight hydrocarbon.

Odor threshold Not available.

pH Not applicable.

Melting point/freezing point > 5000 °F (> 2760 °C)

Initial boiling point and boiling Not applicable.

range

Flash point 410.0 °F (210.0 °C)
Evaporation rate Not applicable.
Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

(%)

Flammability limit - upper

Flammability limit - lower

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not applicable.

Vapor density Not applicable.

Vapor density Not appl Relative density 0.3 - 1.8

Solubility(ies)

Solubility (water) < 0.1 % (Insoluble.)

Partition coefficient (n-octanol/water)

Not available.

0.6

7

Auto-ignition temperature Not applicable

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Graphite (CAS 7782-42-5)

Acute Oral

LD50 Rat > 10000 mg/kg

GRAFOIL® Injectable Packing Containing Oil
942458 Version #: 01 Revision date: - Issue date: 02-February-2018

Components Species Test Results

Triphenyl phosphate (CAS 115-86-6)

Acute Oral

LD50 Rat 3500 mg/kg

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation.

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory

occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Risk of cancer cannot be excluded with prolonged

exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Crystalline silica (quartz) (CAS 14808-60-7)

Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (quartz) (CAS 14808-60-7)

Cancer

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Triphenyl phosphate (CAS 115-86-6)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 0.86 - 1.2 mg/l, 48 Hours
Fish LC50 Fathead minnow (Pimephales promelas) 0.87 mg/l, 96 Hours

Rainbow trout, donaldson trout 0.3 mg/l, 96 Hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of this substance.

Bioaccumulative potential

GRAFOIL® Injectable Packing Containing Oil
942458 Version #: 01 Revision date: - Issue date: 02-February-2018

Partition coefficient n-octanol / water (log Kow)

Triphenyl phosphate (CAS 115-86-6) 4.59

Mobility in soil The product is insoluble in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Triphenyl phosphate (CAS 115-86-6) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Crystalline silica (quartz) (CAS 14808-60-7)

Cancer lung effects

immune system effects

ininiane system enec

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Triphenyl phosphate (CAS 115-86-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations For more information go to www.P65Warnings.ca.gov.

GRAFOIL® Injectable Packing Containing Oil
942458 Version #: 01 Revision date: - Issue date: 02-February-2018

US. Massachusetts RTK - Substance List

Crystalline silica (quartz) (CAS 14808-60-7)

Graphite (CAS 7782-42-5)

Triphenyl phosphate (CAS 115-86-6)

US. New Jersey Worker and Community Right-to-Know Act

Crystalline silica (quartz) (CAS 14808-60-7)

Graphite (CAS 7782-42-5)

Triphenyl phosphate (CAS 115-86-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline silica (quartz) (CAS 14808-60-7)

Graphite (CAS 7782-42-5)

Triphenyl phosphate (CAS 115-86-6)

US. Rhode Island RTK

Crystalline silica (quartz) (CAS 14808-60-7)

Graphite (CAS 7782-42-5)

Triphenyl phosphate (CAS 115-86-6)

California Proposition 65



WARNING: This product can expose you to Crystalline silica (quartz), which is known to the State of California

to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

l.....

Crystalline silica (quartz) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline silica (quartz) (CAS 14808-60-7) Triphenyl phosphate (CAS 115-86-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 02-February-2018

Revision date - 01

NFPA ratings



942458 Version #: 01 Revision date: - Issue date: 02-February-2018

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

NeoGraf Solutions cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.